



UpWind progress in remote sensing of the wind using lidars and sodars

Ejsing Jørgensen, Hans; Courtney, Michael; Mikkelsen, Torben; Antoniou, Ioannis; Bradley, S.; Hunerbein, S. Von; Perez, I.M.; Arranz, P.G.; Foussekis, D.; Harris, M.

Publication date:
2008

Document Version
Publisher's PDF, also known as Version of record

[Link back to DTU Orbit](#)

Citation (APA):
Ejsing Jørgensen, H., Courtney, M., Mikkelsen, T., Antoniou, I., Bradley, S., Hunerbein, S. V., Perez, I. M., Arranz, P. G., Foussekis, D., & Harris, M. (2008). *UpWind progress in remote sensing of the wind using lidars and sodars*. Abstract from 2008 European Wind Energy Conference and Exhibition, Brussels, Belgium.
http://www.risoe.dk/rispubl/art/2008_32.pdf

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

Session: Poster Session + Poster Award + Scientific Award + Excellent young wind doctor award (PO.210)

Track: Technical

UPWIND PROGRESS IN REMOTE SENSING OF THE WIND USING LIDARS AND SODARS (abstract-ID: 464)

Hans E. Joergensen (Risø DTU, Windenergy, Denmark)

Michael Courtney, Denmark (1) Torben Mikkelsen, United Kingdom (1) Ioannis Antoniou, Spain (1) Stuart Bradley, Greece (2) Sabine Von Hunerbein, United Kingdom (2)

Ignacio Marti Perez, (3) Paula Gomez Arranz, (3) Dimitri Foussekis, (4) Mike Harris, (5)

(1) Risø DTU (2) University of Salford (3) CENER (4) CRES (5) QinetiQ

Multi-megawatt wind turbines have created the need to measure the wind speed at 100 m and above including the whole rotor. Development of LIDAR and SODARS has made remote sensing an attractive alternative to high met masts and a growing interest for the introduction of these techniques in wind energy is therefore present.

The UPWIND EU-project work package 6 deals with remote sensing measurements. The scope is to gather the existing experience in this field, generate new and eventually create the basis for the introduction of these techniques in wind energy.

This paper describes an overview of the progress achieved in the UPWIND EU-project work package 6 after approximately two years.

The UPWIND Remote sensing work package are currently investigating three different types of remote sensing

- 1) Mono static SODARS
- 2) Bi static SODARS
- 3) LIDARS (Qinetiq) in the form of focusing laser Doppler systems

In the investigations of the Mono static SODAR the WISE project have shown that there is an urgent need for a calibration method of SODARS. The alternative otherwise is to supplement the SODAR's with a met-tower for calibration. Salford University has been developing a test and calibration method for the loudspeaker arrays in SODARS for testing signal to noise relations including the beam patterns. An atmospheric model is used to simulate responses for different configurations of SODAR arrays. Part of this work has been finished and investigations are now performed for calculation of the signal return for different situations which might enable a real calibration method to be applied for SODAR's.

The Bistatic sodar is under development and theoretical understanding of the system has been achieved. The Bistatic SODARS measures in one volume in contrast to both the lidar and monostatic Sodar systems. This method therefore has an advantage in complex terrain. The progress on the system here reported, showing a much higher sensitivity compared to monostatic SODAR systems.

The focusing LIDAR system Zephir from Qinetiq have been deployed in both flat and complex terrain and compared to met masts. A comprehensive understanding of the LIDAR have been obtained during these campaigns

In the flat terrain experiments comparisons up to 100 m have shown that the cloud correction method for signals have biased the measured wind speeds towards a lower wind speed and new method has been developed to correct the measured signals.

The results from the complex comparisons campaign is reported. Preliminary results show that there is a significant underestimation of the wind speeds which partly is due to the measurement volume compared to a single point measurement. Methods for describing this difference theoretically are currently being developed. Here the size of the estimated systematic error can be calculated giving a terrain, mast and lidar position and measurement height.
